

Woven Coated Polyethylene

Product	Polyethylene Laminated Fabric
Weight (m ²)	80 g/m ²
Colour	Natural
Use	Multi Use

Properties	Test Method	Results
Tape	Type	Woven
	Colour	Natural
	Pick Count (inch) Warp x Weft	8x8
Coating	UV	
	Colour	Transparent/White/Silver LDPE
	Corona	x
	Side	Both side Single Coating
	Coating Weight	24 g/m ²
	FR	x
Packing	Type	Roll
	Bobbin I.D.	
	Length	
	Shipping Mark	

PERFORMANCE			
Property	Test Method	Results	
Tensile Grab Strength	ASTM D 751-2008	Warp: 74 lb	Weft: 65 lb
Elongation		Warp: 24%	Weft: 23%
Tear Strength (Trapezoid)	ASTM D 4533-2004	Warp: 21.3 lb	Weft: 16 lb
Bursting Strength (Diaphragm)	ASTM D 751-2008	114 psi	
Hydrostatic Resistance	ASTM D 751	Kpa	

DISCLAIMER: Information is offered as a service and should not be construed as a recommendation and/or as engineering advice, nor does it represent an expression of performance or implied warranty. We do not assume liability whatsoever in regard to its use. The end user should determine, for itself, the suitability of the product above for the particular purpose and application to which the product will be applied.